

# Lutron® | Rania® digital dimmer with remote control






## Rania IR

For 230 V loads, multiway

Max. 500 W, min. 50 W

For 230 V and 12 V loads, multiway

Max. 450 W/VA, min. 50 W/VA




## Rania IR dual

For 230 V or 12 V loads, multiway

Max. 2 x 250 W/VA, min. 2 x 50 W/VA

# Lutron® | Rania® digital dimmer with remote control



## Product family features:

- Single and dual dimmer available
- Green LEDs indicate light level
- Lights softly fade to on/off
- Auto load-sensing capability
- Acoustically quiet operation
- Dim your light from up to 10 locations (requires accessory dimmers)
- Double-tap to full on
- Memorises last light level
- Replaces a standard switch
- Full family of products for all modern lighting sources
- Family includes wiring accessories

## Specifications for single and dual dimmer:


- 220 - 240 VAC, 50/60 Hz
- Capacity
  - Single dimmer for 230 V loads only: Max. 500 W, min. 50 W
  - Single dimmer for 230 V and 12 V loads (universal): 450 W/VA, min. 50 W/VA
  - Dual dimmer for 230 V loads only: Max. 2 x 250 W, min. 50 W
  - Dual dimmer for 230 V and 12 V loads (universal): Max. 2 x 250 W/VA, min. 2 x 50 W/VA
- CE approved
- Universal dimmer available with leading and trailing edge capability
- Auto-reset thermal overload protection
- Auto-reset short-circuit and over-current protection
- Lightning strike surge protection (6 kV, 200 A)
- 10-year power-failure memory
- Voltage regulation
- Wall box with a depth of at least 32mm recommended; square wall box required for dual dimmer
- Precise colour consistency

## High load and fluorescent interfaces for use with RISI and RIDI dimmers

- To increase load capacity:
  - Max. 1840 W of 230 V loads, use RN-PB-B-AW-M
  - Max. 1200 W/VA of 12 V loads, use NGRX-ELVI-CE-WH-CGP1858
- To control fluorescent loads, use GRX-TVI-CGP1859; Max. switched load 10A, 0-10 V output rating  
10 A - 300 mA sinks current only (max. 150 ballasts)

# Lutron® | Rania® digital dimmer with remote control

## Rania IR dimmer



### Operation

LEDs indicate light level.


### IR receiver

**On/Off tapswitch:** Fades lights on or off.

**TURN ON:** Tap once (lights fade to the preset level), tap twice (lights turn on to full brightness).

**TURN OFF:** Tap once (lights fade-to-off), press and hold (for delayed fade-to-off).

## Rania accessory dimmer




### Multi-location dimming

For use with multi-location dimming only – use up to nine accessory dimmers with one Rania IR multi-location dimmer.

### Ganging and derating

When ganging this product with other Lutron dimmers derate maximum capacity to 350 W/VA.



Use Lutron 2-gang or 3-gang frames to gang Lutron dimmers and wiring accessories.

Point the transmitter at the Rania IR dimmer(s), then use the buttons as outlined below.

**ON FULL:** Tap once - lights brighten smoothly to full brightness.

**OFF:** Tap once: 3 sec fade to off. Press and hold: 10-60 second delayed fade to off.


**BRIGHTEN:** Press to brighten lights.

**DIM:** Press to dim lights.



**ONE-TOUCH BUTTON:** Tap once to recall your favourite light level.

This transmitter is compatible with most learning remote controls.

## Rania IR single dimmer



## Rania IR dual dimmer



For multi-location wiring diagram please refer to Rania installation instructions.

# Choosing your dimmer

You know the mood you want. The next question is: how do you create it? Here's how to choose the right dimmers for your project.




## Step 1

Choose the style and colour that best matches or complements the décor of the room.

## Step 2

Choose the dimmer designed to control the kind of lights you have in the room, for example, incandescent or low voltage.

### Types of lighting


	<b>INC</b>		<b>MVH</b>		<b>LV</b>
	Incandescent 230/240 V		Mains voltage halogen 230/240 V		Electronic and magnetic low voltage 12 V

## Step 3


Calculate the total load.

Incandescent light bulbs have wattage ratings marked on the bulb. Add up the wattage of all the bulbs in the fixture and select a dimmer that is rated above or equal to your total wattage.


### Incandescent 230/240 V



### Mains voltage halogen 230/240 V




### Electronic and magnetic low voltage 12 V




#### Step 4

Decide how many dimmers/switches control the same light fixture and choose from these options.

**If there is only one switch, use a single-pole dimmer** to dim a light from one location. (2-way or multi-location dimmers will work in this application.)



**Multi-location dimming** to dim a light from more than one location – up to ten. Choose one Rania IR dimmer and up to nine Rania accessory dimmers. Accessory dimmers work together with the intelligent dimmer, enabling more than one control to dim a light fixture.



Step 1	Step 2			Step 3	Step 4		
Product	INC 230/240 V	MVH 230/240 V	LV 12 V	Load	1 way	2 way	Multi way
Rania IR single (INC)	x	x		500 W	x	x	x
Rania IR single	x	x	x	450 W/VA	x	x	x
Rania IR dual	x	x	x	2 x 250 W/VA	x	x	x

# Ordering your dimmer

Here is an example of how to order Rania IR dimmers for the look and function you desire.

Rania IR	RI	} — <b>RISU-452B-FAW-M</b>
Rania IR dimmer and remote kit (available in blister pack only)	RP	
Single	S	
Dual	D	
Incandescent (INC)/Mains voltage halogen (MVH)	I	
Universal (INC / MVH and low voltage halogen)	U	
Capacity dual 2 x 250 W/VA	25	
Capacity single Universal model: 450 W/VA Incandescent model: 500 W	45	
2-way / Multi-location	2	
Hanging blister pack Box packaging	H B	
Insert + Frame	I	
Frameless	F	
Faceplate colour	AW	
Arctic White (AW)		
Argentum (AR)		
Mica (MC)		
Satin Nickel (SN)		
Bright Chrome (BC)		
Bright Brass (BB)		
Language of installation instructions	M	
Multilanguage (M)		
Chinese (C)		
English (E)		
Spanish/Portuguese (S)		



**Rania IR dimmer**  
Shown in Arctic White  
Model # RISU-452B-FAW-M



To order remote control only  
Hanging blister pack RIS-REMOTH-AW-\_\*  
Box packaging RIS-REMOTB-AW-M  
Colour: Arctic White (AW)  
38.5 x 117 x 14.5mm

\* Select language of installation instructions

## Colour options



Arctic White (AW)    Argentum (AR)    Mica (MC)

## Metals



Satin Nickel (SN)    Bright Chrome (BC)    Bright Brass (BB)

Other colours and finishes available upon request.

# Ordering your accessories



**Single switch**  
2-way, 250 V / 10 A



**Dual switch**  
2-way, 250 V / 10 A



**Intermediate switch**  
4-way, 250 V / 10 A




**Phone/tv jack**

Product	Model number
Single switch	RN-SS10-X-SYY-Z
Dual switch	RN-DS10-X-SYY-Z
Intermediate switch	RN-IS10-X-SYY-Z
16 A schuko socket	RN-RF16-X-IYY-Z
16 A French socket	RN-RE16-X-IYY-Z
13 A UK switched socket	RN-SRSU-X-FYY-Z
Twin UK switched socket	RN-DRSU-X-FYY-Z
10 A Chinese socket	RN-RC10-X-FYY-Z
UK phone jack	RN-UKPJ-X-FYY-Z
RJ11 phone jack cat 3	RN-RJ11-X-SYY-Z
French phone jack	RN-FRPJ-X-IYY-Z
RJ45 network jack cat 5	RN-RJ45-X-SYY-Z
SAT jack (75 Ohm)	RN-TF75-X-SYY-Z
Triplexer – terminated	RN-TRI1-X-IYY-Z
Triplexer – intermediate	RN-TRI2-X-IYY-Z
2-port frame (frame only)	RN-2PFR-X-SYY-Z
RJ11 connector	CON-1P-C3-YY
RJ45 connector cat 5	CON-1P-C6-YY
RJ45 connector cat 6	CON-1P-C5E-YY
Coax cable connector	CON-1C-YY
BNC jack	CON-1B-YY
MT-RJ fibre jack	CON-1F-MTRJ-YY
SC simplex fibre jack	CON-1F-SC-YY
LC fibre jack	CON-1F-LC-YY
ST fibre jack	CON-1F-ST-YY
1 gang frame	RN-1GANG-X-YY-Z
2 gang frame	RN-2GANG-X-YY-Z
3 gang frame	RN-3GANG-X-YY-Z
Blank faceplate	RN-BLFP-X-SYY-Z


## Key to model numbers:

**RN-SS10-X-SYY-Z**



## Example:

**RN-SS10-B-FAW-M**



## X = Package type

B = Boxes  
H = Hanging clamshell

## YY = Colour/finish

AW = Arctic White  
AR = Argentum  
MC = Mica  
SN = Satin Nickel  
BC = Bright Chrome  
BB = Bright Brass

## S = Frame style

F = Frameless  
I = Frame inset

## Z = Language code

For boxes select:  
M = Multi-language  
(Chinese, Dutch, English, French, German, Italian, Portuguese, Spanish)

## For hanging clamshells:

E = English  
S = Spanish  
C = Chinese



Lutron Electronics Co., Inc.  
©08/2006 Lutron Electronics Co., Inc.  
[www.lutron.com/europe](http://www.lutron.com/europe)  
[www.lutron.com/asia](http://www.lutron.com/asia)  
P/N 367-1033/EA